

UNIS Valjaonica HVT- Cold Rolling Mill

Coil Weight 24 Ton

Width 1.320 mm

Thickness Range 6 – 0,2 mm

FOR SALE BY  
PRIVATE TREATY

Combined

# Tempering & Tension Levelling Line CLECIM (Siemens –VAI CLECIM)



★ ONE LINE LEFT—SPECIAL PRICE ★

**cbi**  
industrial asset management

Jan van Goyenkade 10 ■ 1075 hp  
AMSTERDAM ■ The Netherlands  
T. + 31 20 470 0989 ■ F. + 31 20 470 2084  
info@cbiworld.com ■ www.cbiworld.com

Sale held in conjunction with:

**NATIONAL  
MACHINERY  
EXCHANGE, INC.**



# 20-HI Sendzimir Reversing Cold Rolling Mill WATERBURY FARREL



20-Hi "SENDZIMIR"

Reversing

Cold Rolling Mill

WATERBURY FARREL

Model ZR22B 52"

Max. Strip Width  
1.320 mm; Max Coil  
Weight 24 Ton

Max Incoming Thick-  
ness 6 mm; Max. Out-  
going Thickness 0,2  
mm;

Speed 0-762 M/Min;  
Mill Drive Motors 2 x  
1.840 kW;

Unwinder & Rewinder  
Motors, each 2 x  
1.840kW.



# Combined Tempering & Tension Levelling Line CLECIM (Siemens –VAI CLECIM)



Min/Max Strip Width: 600 - 1.300 mm;  
Strip Thickness Range 0,2 – 1,5 mm

- ◆ Entry-Hydr. Coil Car “CLECIM”
- ◆ Payoff “CLECIM”
- ◆ Threading Unit “CLECIM”
- ◆ Exit Leveller “CLECIM”
- ◆ Threading Strip Unit “CLECIM”
- ◆ Welder with Hydr. Clamping “CLECIM”
- ◆ Strip Edge Slitter “CLECIM”
- ◆ Strip Pull-Through Unit “CLECIM”

- ◆ S-Rolls “CLECIM”
- ◆ 4-High Temper Mill “CLECIM”
- ◆ Tension Levelling Rolls “CLECIM”
- ◆ Electric Strip Oiler “ST Peabody”
- ◆ Exit Shear “CLECIM”
- ◆ Rewinder “CLECIM”







# NATIONAL MACHINERY EXCHANGE, INC.

158 PARIS STREET, NEWARK,  
NEW JERSEY 07105-4397  
TELEPHONE: 973-344-6100 / FAX:  
973-589-0944

WEBSITE:  
[WWW.NATIONALMACHY.COM](http://WWW.NATIONALMACHY.COM)

E-MAIL:  
[SALES@NATIONALMACHY.COM](mailto:SALES@NATIONALMACHY.COM)

INSPECTION POSSIBLE

Contact: [INFO@cbiworld.com](mailto:INFO@cbiworld.com)

or phone: + 31 20 470 0989

Technical Documentation available  
in the works

C.B.I. industrial asset management BV  
Jan van Goyenkade 10  
1075 HP AMSTERDAM  
The Netherlands

T. + 31 20 470 0989 ■ F. + 31 20 470 2084  
[info@cbiworld.com](mailto:info@cbiworld.com) ■ [www.cbiworld.com](http://www.cbiworld.com)